




JOHN DEERE

PowerTech™

3029T Diesel Engine

for Generator Set Applications



3029TF Engine shown

General Data

Model	3029TF120	Aspiration	Turbocharged
Number of cylinders	3	Length-- mm (in)	716 (28.2)
Displacement-- L (cu in)	2.9 (177)	Width-- mm (in)	519 (20.4)
Bore and Stroke-- mm (in)	106 x 110 (4.17 x 4.33)	Height-- mm (in)	819 (32.2)
Compression Ratio	17.2:1	Weight, dry-- kg (lb)	316 (697)
Engine Type	In-line, 4-Cycle		

Ratings

Prime power at 50 Hz (1500)	38 kW (51 hp)
Standby power at 50 Hz (1500)	42 kW (56 hp)

Prime power is the nominal power an engine is capable of delivering with a variable load for an unlimited number of hours per year. This rating conforms to ISO 3046 and SAI J1995.

Standby power is the nominal engine power available at varying load factors for up to 500 hours per year. This rating conforms to ISO 3046 and SAE J1995. The calculated generator set rating range for standby applications is based on minimum engine power (nominal -5%) to provide 100% meet-or-exceed performance for assembled standby generator sets.


Certifications

- Non-Emissions Certified

Dimensions



Performance curve



Performance data

Hz (rpm)	Generator efficiency %	Fan power		Power factor	Calculated generator set output			
		kW	hp		Prime		Standby	
					kWe	kVa	kWe	kVa
50 (1500)	88-92	2.0	2.7	0.8	32-33	40-41	35-37	44-46

Features and Benefits

Dynamically Balanced Crankshaft

- Induction-hardened journals for long hours of reliable service
- Robust design to drive machinery from the front of the crankshaft
- Supported by five main bearings

Forged-Steel Connecting Rods

- 45-degree connecting rod/cap-joint design allows the use of large connecting rod bearings for increased durability

Replaceable Wet-type Cinder Liners

- Provide excellent heat dissipation
- Precision machined for long life
- Rebuild to original specifications

Easy to Apply, Easy to Install

- Front and rear engine mounting pads on the side of the block facilitates installations
- All connection points in common locations make it easy to install or package

Compact Size

- Short length is ideal for both skid and packaged installations
- High mount or low mount turbocharger position to meet packaging requirements

World-class Performance

- Excellent fuel economy and low oil consumption

Fuel System Controls

- Proven and Reliable Mechanical Governor
- 3-5% Droop Governing
- 12V or 24V Electric Shutoff



John Deere Power Systems
3801 W. Ridgeway Ave.
PO Box 5100
Waterloo, IA 50704-5100
Phone: 800.553.6446
Fax: 319.292.5075

John Deere Power Systems
Usine de Saran
La Foulonnerie - B.P. 11.13
45401 Fleury les Aubrais Cedex
France
Phone: 33.2.38.82.61.19
Fax: 33.2.38.82.60.00