

17 Harry Pichanick Drive  
Alex Park  
Harare

Tel: + 263 4 744759  
Cell: +263 77 2 515919  
Cell: +27 82 856 0393



**Radzim Agri-Power**

**JOHN DEERE**

**JD45GO**

GENERAL DATA	
Model	JD45GO
Continuous / Prime power (P.R.P)	40,00 kVA
Continuous / Prime power (P.R.P)	32,00 kW
Stand-by power (L.T.P)	44,00 kVA
Stand-by power (L.T.P)	35,20 kW
Power Factor / Cos (φ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases (with Neutral)
Engine Speed	1500 rpm

DIMENSIONS*	
Length (-L- m)	2260 mm
Width (-W- m)	1040 mm
Height (-H- m)	1450 mm
Weight (kg)	980 kg
Tank Capacity	160 l

ENGINE	
Brand	JOHN DEERE
Model	3029TF158
No. of Cylinders	3
Cubic capacity	2,9 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	36 kW
BMEP	1036 kPa
SAE:	3-11½

ENGINE TECHNICAL DATA	
Oil Qty	9 l
Antifreeze Qty	14,5 l
Cooling air flow	N/A
Combust. air flow	3 m <sup>3</sup> /min
Exhaust gas flow	7 m <sup>3</sup> /min

FUEL CONSUMPTION @ LOAD	
100% (Standby)	14,1 l/h
100% (Prime)	12,9 l/h
75%	10,6 l/h
50%	7,1 l/h
25%	3,5 l/h



ALTERNATOR	
Brand	MARELLI
Model	MJB200SA4
Continuous power	40,00 kVA
Stand-by power	44,00 kVA
Connection	Stella Series

STARTING BATTERY	
Capacity	100 Ah
Quantity	1
Voltage	12 V

FLEXIBLE PIPE	
Model	DN50
Quantity	1
Diameter	60 mm

EXHAUST SILENCER	
Model	MSR/a 50
Quantity	1
Diameter	60 mm

\* Figures are subject to change without prior notice.

\*\* The mentioned power values are according to ISO8528-1 Standards