

17 Harry Pichanick Drive  
Alex Park  
Harare

Tel: + 263 4 744759  
Cell: +263 77 2 515919  
Cell: +27 82 856 0393



## Radzim Agri-Power

### PERKINS

### P130GO

#### GENERAL DATA

Model	P130GO
Continuous / Prime power (P.R.P)	127,00 kVA
Continuous / Prime power (P.R.P)	101,60 kW
Stand-by power (L.T.P)	139,00 kVA
Stand-by power (L.T.P)	111,20 kW
Power Factor / Cos (φ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases (with Neutral)
Engine Speed	1500 rpm

#### DIMENSIONS\*

Length (-L- m)	3060 mm
Width (-W- m)	1140 mm
Height (-H- m)	1660 mm
Weight (kg)	2040 kg
Tank Capacity	360 l

#### ENGINE

Brand	PERKINS
Model	1006TAG
No. of Cylinders	6
Cubic capacity	5,99 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	121 kW
BMEP	1767 kPa
SAE:	2-11½

#### ENGINE TECHNICAL DATA

Oil Qty	19 l
Antifreeze Qty	37,22 l
Cooling air flow	154 m <sup>3</sup> /min
Combust. air flow	8,38 m <sup>3</sup> /min
Exhaust gas flow	24,14 m <sup>3</sup> /min

#### FUEL CONSUMPTION @ LOAD

100% (Standby)	34,6 l/h
100% (Prime)	31,5 l/h
75%	24,1 l/h
50%	16,5 l/h
25%	N/A



#### ALTERNATOR

Brand	MARELLI
Model	MJB225LA4
Continuous power	127,00 kVA
Stand-by power	139,00 kVA
Connection	Stella Series

#### STARTING BATTERY

Capacity	100 Ah
Quantity	1
Voltage	12 V

#### FLEXIBLE PIPE

Model	DN75
Quantity	1
Diameter	89 mm

#### EXHAUST SILENCER

Model	MSR/a 80
Quantity	1
Diameter	89 mm

\* Figures are subject to change without prior notice.

\*\* The mentioned power values are according to ISO8528-1 Standards