

17 Harry Pichanick Drive  
Alex Park  
Harare

Tel: + 263 4 744759  
Cell: +263 77 2 515919  
Cell: +27 82 856 0393



# Radzim Agri-Power

## PERKINS

## P210GO

### GENERAL DATA

Model	P210GO
Continuous / Prime power (P.R.P)	208,00 kVA
Continuous / Prime power (P.R.P)	166,40 kW
Stand-by power (L.T.P)	229,00 kVA
Stand-by power (L.T.P)	183,20 kW
Power Factor / Cos (φ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases (with Neutral)
Engine Speed	1500 rpm

### DIMENSIONS\*

Length (-L- m)	3060 mm
Width (-W- m)	1140 mm
Height (-H- m)	1970 mm
Weight (kg)	2350 kg
Tank Capacity	360 l

### ENGINE

Brand	PERKINS
Model	1306CE87TAG3
No. of Cylinders	6
Cubic capacity	8,7 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	180 kW
BMEP	1683 kPa
SAE:	2-11½

### ENGINE TECHNICAL DATA

Oil Qty	28,3 l
Antifreeze Qty	37,2 l
Cooling air flow	375 m <sup>3</sup> /min
Combust. air flow	13,5 m <sup>3</sup> /min
Exhaust gas flow	36,5 m <sup>3</sup> /min

### FUEL CONSUMPTION @ LOAD

100% (Standby)	49,1 l/h
100% (Prime)	45,2 l/h
75%	35 l/h
50%	24 l/h
25%	N/A



### ALTERNATOR

Brand	MARELLI
Model	MJB250LA4
Continuous power	220,00 kVA
Stand-by power	240,00 kVA
Connection	Stella Series

### STARTING BATTERY

Capacity	100 Ah
Quantity	1
Voltage	12 V

### FLEXIBLE PIPE

Model	DN75
Quantity	1
Diameter	89 mm

### EXHAUST SILENCER

Model	MSR/a 80
Quantity	1
Diameter	89 mm

\* Figures are subject to change without prior notice.

\*\* The mentioned power values are according to ISO8528-1 Standards