

17 Harry Pichanick Drive  
Alex Park  
Harare

Tel: + 263 4 744759  
Cell: +263 77 2 515919  
Cell: +27 82 856 0393



## Radzim Agri-Power

### PERKINS

### P65GO

#### GENERAL DATA

Model	P65GO
Continuous / Prime power (P.R.P)	60,00 kVA
Continuous / Prime power (P.R.P)	48,00 kW
Stand-by power (L.T.P)	66,00 kVA
Stand-by power (L.T.P)	52,80 kW
Power Factor / Cos (φ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases (with Neutral)
Engine Speed	1500 rpm

#### DIMENSIONS\*

Length (-L- m)	2260 mm
Width (-W- m)	1040 mm
Height (-H- m)	1375 mm
Weight (kg)	1100 kg
Tank Capacity	160 l

#### ENGINE

Brand	PERKINS
Model	1103A-33TG2
No. of Cylinders	3
Cubic capacity	3,3 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	53,8 kW
BMEP	1333 kPa
SAE:	3-11½

#### ENGINE TECHNICAL DATA

Oil Qty	8,3 l
Antifreeze Qty	10,2 l
Cooling air flow	89 m <sup>3</sup> /min
Combust. air flow	3,8 m <sup>3</sup> /min
Exhaust gas flow	10,1 m <sup>3</sup> /min

#### FUEL CONSUMPTION @ LOAD

100% (Standby)	15,4 l/h
100% (Prime)	13,9 l/h
75%	10,4 l/h
50%	7,2 l/h
25%	4,1 l/h



#### ALTERNATOR

Brand	MARELLI
Model	MJB200MA4
Continuous power	59,50 kVA
Stand-by power	65,50 kVA
Connection	Stella Series

#### STARTING BATTERY

Capacity	100 Ah
Quantity	1
Voltage	12 V

#### FLEXIBLE PIPE

Model	DN50
Quantity	1
Diameter	60 mm

#### EXHAUST SILENCER

Model	MSR/a 50
Quantity	1
Diameter	60 mm

\* Figures are subject to change without prior notice.

\*\* The mentioned power values are according to ISO8528-1 Standards