

17 Harry Pichanick Drive
Alex Park
Harare

Tel: + 263 4 744759
Cell: +263 77 2 515919
Cell: +27 82 856 0393



Radzim Agri-Power

PERKINS

P730U

GENERAL DATA	
Model	P730U
Continuous / Prime power (P.R.P)	750,00 kVA
Continuous / Prime power (P.R.P)	600,00 kW
Stand-by power (L.T.P)	825,00 kVA
Stand-by power (L.T.P)	660,00 kW
Power Factor / Cos (φ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases (with Neutral)
Engine Speed	1500 rpm

DIMENSIONS*	
Length (-L- m)	4000 mm
Width (-W- m)	2100 mm
Height (-H- m)	2100 mm
Weight (kg)	7300 kg
Tank Capacity	N/A

ENGINE	
Brand	PERKINS
Model	4006-23TAG2A
No. of Cylinders	6
Cubic capacity	22,921 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	632 kW
BMEP	
SAE:	

ENGINE TECHNICAL DATA	
Oil Qty	
Antifreeze Qty	
Cooling air flow	
Combust. air flow	
Exhaust gas flow	

FUEL CONSUMPTION @ LOAD	
100% (Standby)	176 l/h
100% (Prime)	161 l/h
75%	122 l/h
50%	83 l/h
25%	N/A



ALTERNATOR	
Brand	MARELLI
Model	MJB355MB4
Continuous power	800 kVA
Stand-by power	880 kVA
Connection	Stella Series

STARTING BATTERY	
Capacity	220 Ah
Quantity	2
Voltage	24 V

FLEXIBLE PIPE	
Model	DN150
Quantity	2
Diameter	168 mm

EXHAUST SILENCER	
Model	MS 35
Quantity	2
Diameter	168 mm

* Figures are subject to change without prior notice.

** The mentioned power values are according to ISO8528-1 Standards